CPL LESSON 114 GENERAL FLYING - C182 STOL

Elem	ents	Performance Criteria	Stnd Rqd	Stnd Achieved
A1.1	Start & Stop	Clears aircraft from obstructions, buildings and other aircraft		
	Engine	Clears propeller before start	1	
		Starts engine in accordance with Flight Manual/POH including hot and cold starts		
		Performs after-start checks from memory in accordance with approved checklist 11		
		Manages start and after-start emergencies from memory in accordance with Flight Manual/POH		
		Shuts down engine in accordance with Flight Manual/POH		
		Performs after-shutdown checks in accordance with approved checklist ¹²		
		Exercises propeller care and manages adverse effects of propeller wash		
		Complies with manufacturer's limitations and reports deviations when appropriate.		
A1.2	Taxi Aeroplane	Requests applicable ATC clearances or CTAF broadcasts in accordance with AIPs		
		Confirms serviceability of brakes after park brake release and before taxiing	1	
		Interprets and complies with taxiway and other aerodrome markings. Note: In the absence of markings, the aircraft is maintained in the centre of the taxiway and at a safe ¹³ distance from obstacles		
		Maintains lookout and right-of-way rules and complies with ATC or marshalling instructions when applicable		
		Adjusts taxi speed to suit aeroplane type, surface conditions, level of congestion, and maintenance of control and to avoid collision with obstacles or other aircraft		
		Applies flying controls, power and brakes to maintain the aircraft on the taxiway centreline (±1.5 metres of centreline) while compensating for wind and surface conditions		
		Performs instrument checks in a suitable area clear of traffic and other hazards		
		Ensures final approach path is clear of conflicting traffic on specified or appropriate runway.		
A2.1	Carry out pre-	Performs approved pre-take-off checklist		
	take off	Performs take-off safety brief prior to runway entry	1	
	procedures	Requests and complies with ATC clearance or broadcast intentions as applicable		
		Ensures final approach path is clear of conflicting traffic on specified or appropriate runway		
		Configures aircraft for take-off and lines up on the centreline at appropriate intersection or full length of runway		
		Aligns aircraft on the centreline of the specified or appropriate runway		
		Performs approved <u>line-up checks</u> .		

¹¹ A checklist derived from information set out in the Flight Manual/POH, placards or other documents provided with the aircraft, necessary to ensure the <u>safe</u> operation of the aircraft

¹² A checklist derived from information set out in the Flight Manual/POH, placards or other documents provided with the aircraft, necessary to ensure the <u>safe</u> operation of the aircraft

¹³ Means that a manoeuvre or flight is completed without injury to persons, damage to aircraft or breach of aviation safety regulations, while meeting the requirements of the Manual of Standards Part 61.

CPL LESSON 114 CONT GENERAL FLYING - C182 STOL

Elements		Performance Criteria	Stnd Rqd	Stnd Achieved
A2.2	Take Off Aeroplane	Sets take-off power and confirms engine is operating within limits	1	
		Accelerates aircraft along the centreline to the take-off safety speed, allowing for wind		
		Rotates aircraft to the target climb attitude at approximately 3° per second		
		Balances aircraft ¹⁴		
		Maintains extended centreline of runway or obstacle clearance flight path (±10°)		
		Maintains nominated climb speed (+5, -0 kts) until clear of obstacles		
		Retracts undercarriage at a <u>safe¹⁵</u> altitude if applicable		
		Retracts flap at a <u>safe</u> altitude if applicable		
		Sets climb power and speed (± 5 kts) in accordance with manufacturer's time limits or at a <u>safe</u> height		
		Rejects take-off for abnormalities prior to reaching take-off safety speed.		
A2.4	Carry out after	Performs after-take-off checks in accordance with approved checklist at a safe height		
	take off	Complies with ATC instructions if applicable	1	
	procedures	Maintains separation from other aircraft.		
A3.6	Perform circuits and approaches	Maintains lookout and traffic separation using a systematic scan technique at a rate determined by traffic density	1	
		Monitors and reacts appropriately to engine performance and indications		
		Tracks upwind along extended runway centreline to 500 ft		
		Establishes aircraft on crosswind tracking 90° to the runway		
		Establishes aircraft on downwind at circuit height (±100 ft) tracking parallel to the runway at a specified distance from the runway		
4		Performs pre-landing checklist		
		Establishes aircraft on base leg a specified distance from threshold of runway		
		Commences and controls rate of descent to maintain approach path		
		Ensures aircraft is aligned with specified or appropriate runway		
		Establishes aircraft on final approach in approach configuration not below 500 ft AGL		
		Identifies and selects aiming point		
		Maintains aircraft on extended centreline and coordinates power and attitude to maintain approach slope and speed not less than 1.3Vs to a height of 50 ft		
		Applies speed allowances for wind gusts when applicable		
		Maintains speed not below threshold speed +10 kts until commencing flare		
		Configures aircraft for landing		
		Performs final approach checklist		
		Anticipates and allows for wind on all legs of the circuit		
		Balances aircraft		
		<u>Trims aircraft</u> .		

The skid ball in the balance indicator is less than a quarter of the ball diameter from the centre.
 Means that a manoeuvre or flight is completed without injury to persons, damage to aircraft or breach of aviation safety regulations, while meeting the requirements of the Manual of Standards Part 61.

CPL LESSON 114 GENERAL FLYING - C182 STOL

Elements		Performance Criteria	Stnd Rqd	Stnd Achieved
A4.1	Land Aeroplane	Identifies and selects aiming point ¹⁶		
		Selects power to idle prior to touchdown	1	
		Flares aircraft at an appropriate height		
		Controls ballooning during flare and bouncing after touchdown by adjustment of attitude without the application of power		
		Touches down at a controlled rate of descent ¹⁷ , aligned with runway centreline		
		Touches down within 200ft/60 metres for CPL beyond a nominated touchdown point		
		Touches down ±2 metres of centreline		
		Touches down on the main wheels, and the nose is lowered onto the runway without harshness		
		Maintains directional control along the centreline		
		Applies braking to stop the aircraft within landing distance available.		
		Performs after-landing checklist		
		Maintains separation from other traffic.		
A5.5	Execute minimum ground roll take-off and landing	Short take-off	ı	
		Calculates take-off and landing performance in accordance with performance chart	1	
		Performs pre-take-off checks in accordance with approved checklist		
		Lines up aeroplane to enable maximum use of runway length		
	+ Soft field Take	Performs <u>line-up checks</u> in accordance with approved checklist		
	Off	Applies take-off power before brakes (where fitted) are released		
		Rotates aeroplane at recommended speed		
4		Sets nominated climb speed appropriate to obstacle clearance requirements		
		Performs after-take-off checks from memory in accordance with approved checklist.		
		<u>Short landing</u>		
		Lands aeroplane at nominated touchdown point +100 ft/30 metres for CPL at minimum speed		
		Controls ballooning during flare and bouncing after touchdown by adjustment of attitude without the application of power		
		Maintains direction after touchdown		
		Applies maximum braking without locking up wheels		
		Stops aircraft within landing distance available		
		Performs after-landing checks in accordance with approved checklist.		

I have completed the training specified in the elements, which have been certified on this Achievement Record					
Candidate's Signature	Date				
Instructor's Signature	Date				

¹⁶ The 'aiming point' related to a visual approach and landing of an aircraft, is that point at which a pilot looks, to achieve a predetermined touchdown point.

^{17 &#}x27;Controlled rate of descent' associated with a landing means that the touchdown is without harshness and the successful outcome of the landing is not in doubt.

08 / 09 Page.